

TORQUE SPECIFICATION

Part tightened		N·m	kgf·cm	ft·lbf
Bleeder plug	Front	7.8	80	69 in.·lbf
	Rear	8.3	85	74 in.·lbf
Hydraulic brake booster clevis lock nut		25	260	19
Brake line union nut		15	155	11
Front brake caliper installation bolt		26	270	20
Flexible hose x Shock absorber bracket		33	340	25
Front disc brake torque plate x Steering knuckle		107	1,090	79
Front disc brake caliper x Flexible hose		30	310	22
Rear drum brake wheel cylinder x Backing plate		10	100	7
ABS actuator bracket x Body		19	195	14
ABS actuator x ABS actuator bracket		20	200	15
Regenerative brake actuator x Body		19	195	14
Hydraulic brake booster x Body		13	130	9
Hydraulic brake booster x Reservoir		1.7	17.5	15.2 in.·lbf
Accumulator x Pump motor		54	550	36
Front speed sensor installation bolt		8.0	80	69 in.·lbf
Front speed sensor wire harness clamp x Body		5.0	55	48 in.·lbf
Front speed sensor wire harness clamp x Shock absorber		5.0	55	48 in.·lbf
Rear speed sensor wire harness clamp x Body		5.0	55	48 in.·lbf
Rear speed sensor wire harness clamp x Suspension Arm		13	130	9